

# ENGINE DRIVEN PETROL



**TE**



## CENTRIFUGAL - SITE WATER

The **TEM-25H** is a self-priming centrifugal pump, powered by a compact and powerful 4 stroke, genuine Honda, petrol engine. This is coupled to a pump end that has an aluminium body, volute and impeller, which ensure that it is light, compact and portable. It is fitted to a sturdy base plate, with rubber feet to minimize vibration and has a comfortable, yet robust, carrying handle. For reliability, the pump is fitted with a carbon ceramic mechanical seal. Suitable for clean and dirty water, it has high head capabilities and gives a good flow of water. It's neat size and performance makes it popular for irrigation, sprinkling, flooded pit drainage, washing down and general pumping. It is not fitted with an engine oil alert system. Maximum suction lift is 8 metres, however 6 metres, or less, is recommended. Hose couplings, washers, clips and strainers are supplied, but hoses are extra.


- Hire fleets
- Construction
- Utilities
- Drainage
- Irrigation
- Wash down

The models **TET2-50HA**, **TE4-80HA** and **TE2-100HA** are all self-priming pumps and are powered by genuine Honda 4 stroke OHV petrol engines. They have carbon ceramic mechanical seals and lightweight, aluminium pump housings, to assist portability. For increased abrasion resistance, they have cast iron volutes and impellers. These materials ensure maximum durability for the pumping of clear and black water as found on building sites. All models are housed within a protective tubular steel, easy carry frame which has anti-vibration mounts fitted. They are fitted with oil alerts, to protect the engines from misuse. These are popular pumps are used by Utilities and are found on many UK hire fleets. Maximum suction lift is 8 metres, however 6 metres, or less, is recommended. Hose couplings, washers, clips and strainers are supplied with all pumps, but hoses are extra.

To assist manual handling of the model **TE2-100HA** a two wheeled site trolley is available as an optional extra.



**TEM-25H**



**TET2-50HA**

model	inlet (mm)	outlet (mm)	engine	fuel	HP	oil alert	flow (l/min)	head (mtrs)	solids (mm)	w x l x h (mm)	dry weight (kgs)	packing weight (kgs)
TEM-25H	25	25	GX25	petrol	1.5	no	140	40	5	215x340x270	5.00	7.00
TET2-50HA	50	50	GX120	petrol	4.0	yes	520	32	6	356x470x350	22.00	25.00
TE4-80HA	80	80	GX160	petrol	5.5	yes	1000	32	6	375x527x420	27.00	30.00
TE2-100HA	100	100	GX240	petrol	8.0	yes	1800	28	6	650x470x620	44.00	50.00
optional extra: residue pumping adaptor kit for 25mm centrifugal pumps only											1.00	2.80
optional extra: site trolley (TE2-100HA)											12.40	12.40